

## 80x80x20mm

Model	P/N	Bearing ● Sleeve ● 2BALL	Rating Voltage (VDC)	Power Current (mA)	Power Consumption (WATTS)	Speed (RPM)	Air Flow (CFM)	Static Pressure (Inch-H <sub>2</sub> O)	Noise (dBA)	Weight (g)
KD1208PKB1	13.(2).GN	●	12	130	1.6	3300	39.0	0.19	39.0	72
KD1208PKB2	13.(2).GN	●	12	110	1.3	3000	35.0	0.17	37.0	72
KD1208PKB3	13.(2).GN	●	12	80	1.0	2600	31.0	0.14	33.0	72
KD1208PKS1	13.GN	●	12	140	1.7	3200	36.0	0.18	38.0	72
KD1208PKS2	13.GN	●	12	110	1.3	2900	33.0	0.16	35.0	72
KD1208PKS3	13.GN	●	12	80	1.0	2500	29.0	0.12	30.0	72
KD2408PKB1	13.(2).A.GN	●	24	62	1.5	3300	39.0	0.19	39.0	72
KD2408PKB2	13.(2).A.GN	●	24	47	1.1	3000	35.0	0.17	37.0	72
KD2408PKB3	13.(2).A.GN	●	24	35	0.8	2600	31.0	0.14	33.0	72
KD2408PKS1	13.A.GN	●	24	61	1.5	3200	36.0	0.18	38.0	72
KD2408PKS2	13.A.GN	●	24	50	1.2	2900	33.0	0.16	35.0	72
KD2408PKS3	13.A.GN	●	24	41	1.0	2500	29.0	0.12	30.0	72

## 80x80x25 mm

Model	P/N	Bearing	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(Inch-H <sub>2</sub> O)	(dBA)	(g)
KD1208PTB1	13.(2).GN	●	12	140	1.7	3100	41.0	0.19	35.0	80
KD1208PTB2	13.(2).GN	●	12	110	1.3	2800	37.0	0.16	32.0	80
KD1208PTB3	13.(2).GN	●	12	80	1.0	2500	33.1	0.13	28.0	80
KD1208PTS1	13.GN	●	12	150	1.8	3000	40.0	0.18	33.0	80
KD1208PTS2	13.GN	●	12	120	1.4	2700	36.5	0.15	31.0	80
KD1208PTS3	13.GN	●	12	90	1.1	2300	31.0	0.11	26.0	80
KD2408PTB1	13.(2).A.GN	●	24	65	1.6	3100	41.0	0.19	35.0	83
KD2408PTB2	13.(2).A.GN	●	24	50	1.2	2800	37.0	0.16	32.0	83
KD2408PTB3	13.(2).A.GN	●	24	37	0.9	2500	33.1	0.13	28.0	83
KD2408PTS1	13.A.GN	●	24	67	1.6	3000	40.0	0.18	33.0	83
KD2408PTS2	13.A.GN	●	24	54	1.3	2700	36.5	0.15	31.0	83
KD2408PTS3	13.A.GN	●	24	44	1.1	2300	31.0	0.11	26.0	83

## 92x92x25 mm

Model	P/N	Bearing	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(Inch-H <sub>2</sub> O)	(dBA)	(g)
KD1209PTB1	13.(2).GN	●	12	160	1.9	2800	49.0	0.17	35.0	95
KD1209PTB2	13.(2).GN	●	12	130	1.6	2600	48.0	0.15	33.0	95
KD1209PTB3	13.(2).GN	●	12	90	1.1	2300	41.0	0.11	30.0	95
KD1209PTS1	13.GN	●	12	160	1.9	2800	49.0	0.16	34.0	95
KD1209PTS2	13.GN	●	12	130	1.6	2500	44.5	0.14	32.0	95
KD1209PTS3	13.GN	●	12	100	1.2	2200	39.0	0.11	28.0	95
KD2409PTB1	13.(2).A.GN	●	24	75	1.8	2800	49.0	0.17	35.0	100
KD2409PTB2	13.(2).A.GN	●	24	60	1.4	2600	48.0	0.15	33.0	100
KD2409PTB3	13.(2).A.GN	●	24	43	1.0	2300	41.0	0.11	30.0	100
KD2409PTS1	13.A.GN	●	24	76	1.8	2800	49.0	0.16	34.0	100
KD2409PTS2	13.A.GN	●	24	61	1.5	2500	44.5	0.14	32.0	100
KD2409PTS3	13.A.GN	●	24	49	1.2	2200	39.0	0.11	28.0	100

## 120x120x38 mm

Model	P/N	Bearing	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(Inch-H <sub>2</sub> O)	(dBA)	(g)
KD1212PMB1	13.(2).A.GN	●	12	525	6.3	2650	132.7	0.26	43.7	245
KD1212PMB2	13.(2).A.GN	●	12	365	4.4	2350	117.6	0.21	40.8	245
KD1212PMB3	13.(2).A.GN	●	12	290	3.5	2050	100.8	0.15	37.0	245
KD2412PMB1	13.(2).A.GN	●	24	270	6.5	2650	132.7	0.26	43.7	245
KD2412PMB2	13.(2).A.GN	●	24	217	5.2	2350	117.6	0.21	40.8	245
KD2412PMB3	13.(2).A.GN	●	24	153	3.7	2050	100.8	0.15	37.0	245

\*All model could be customized on voltage or any other requirements to fit your need.

\*Specifications subject to change without notice. Please Visit SUNON web site at <http://www.sunon.com> for update information.